

XCL-CG Series - XCL-SG Series- Specifications

Basic Specifications	5.1M Camera Link*		5.1M Camera Link*	
	XCL-SG510	XCL-SG510C	XCL-CG510	XCL-CG510C
B/W / Colour	B/W	RAW colour	B/W	Colour
Image Size	5.1 Mega			
Image Sensor	2/3-type CMOS Image sensors with a global shutter function (Pregius)			
Number of Effective Pixels (H x V)	2,464 x 2,056			
Cell Size (H x V)	3.45 μm x 3.45 μm			
Standard Output Pixels (H x V)	2,448 x 2,048			
Colour Filter	-	RGB colour mosaic filter	-	RGB colour mosaic filter
Frame Rate	16 fps (Base, 8 bit, 1tap, Mono/Raw) 32 fps (Base, 8 bit, 2tap, Mono/Raw)* 48 fps (Base, 8 bit, 3tap, Mono/Raw) 64 fps (Medium, 8 bit, 4tap, Mono/Raw) 124 fps (Full, 8 bit, 8tap, Mono/Raw) 154 fps (80 bit(DECA), 8 bit, 10tap, Mono/Raw) *At the time of shipment		14 fps (Base, 8 bit, 1tap, Mono/Raw) 29 fps (Base, 8 bit, 2tap, Mono/Raw)* 35 fps (Base, 8 bit, 3tap, Mono/Raw) *At the time of shipment	
Minimum Illumination	0.5 lx (Iris: F1.4, Gain: +18 dB, Shutter: 1/30 s)	12 lx (Iris: F1.4, Gain: +18 dB, Shutter: 1/30 s)	0.5 lx (Iris: F1.4, Gain: +18 dB, Shutter: 1/30 s)	12 lx (Iris: F1.4, Gain: +18 dB, Shutter: 1/30 s)
Sensitivity	F5.6 (400 lx, Gain: 0 dB, Shutter: 1/30 s)	F5.6 (2000 lx, Gain: 0 dB, Shutter: 1/30 s)	F5.6 (400 lx, Gain: 0 dB, Shutter: 1/30 s)	F5.6 (2000 lx, Gain: 0 dB, Shutter: 1/30 s)
SNR	More than 50 dB Lens close, Gain: 0 dB, 8 bit)			
Gain	Auto, Manual : 0 to 18 dB			
Shutter Speed	Auto, Manual : 60 to 1/100,000 s			
White Balance	-	Manual, One push	-	Manual, One push
Camera features				
Readout Modes	Normal, Binning (2x1, 1x2, 2x2), Partial Scan (Multi ROI)	Normal, Partial Scan (Multi ROI)	Normal, Binning (1x2, 2x1, 2x2)*1, Partial Scan (Multi ROI)	Normal, Partial scan
Readout Features	LUT (Binarization, Gamma (Arbitrary value settable)), Test pattern			
Synchronization	Hardware trigger, Software trigger			
Trigger Modes	OFF (Free run), ON (Edge detection, Trigger width detection), Speed trigger (Burst trigger/Bulk trigger/Sequential trigger)			
Userset	16			
User Memory	32 kbytes + 64 bytes x 16ch		64 bytes x 16ch	
Partial Scan	W (Pixel) H (Line)	1 to 2464 1 to 2056	1 to 2464 1 to 2056	1 to 2464 1 to 2056
GPO	EXPOSURE/Strobe/LVAL/FVAL/Sensor lead out/Trigger through/Pulse generation signal/User defined 1, 2, 3 (Output switching)			
Other Features	Wide dynamic range, Frame accumulation, Area exposure, Area gain, Defect correction, Shading correction, Temperature readout, LUT, 3 x 3 filter		Area gain, Defect correction, Shading correction, Temperature readout, LUT, 3 x 3 filter	
Interface				
Video Data Output	digital Mono 8, 10, 12, 16** bit (at the time of shipping 8bit)	digital Raw 8, 10, 12, 16** bit (at the time of shipping 8 bit)	digital Mono 8, 10, 12 bit (at the time of shipping 8bit)	digital Raw 8, 10, 12 bit (at the time of shipping 8 bit) digital RGB 24 bit
Base Clock (No. of Taps)	85/65/45 MHz switchable		75/45 MHz switchable	
Camera Link Tap	1/2/3/4/8/16 switchable		1/2/3 switchable	
Digital Interface	LVDS			
Camera Specification	Camera Link* Version2.0			
Output Data Clock	85MHz (1, 2, 3, 4, 8, 10tap), 65MHz (1, 2, 3, 4, 8, 10tap), 45MHz (1, 2, 3, 4, 8, 10tap)		75MHz (1, 2, 3tap), 45MHz (1, 2, 3tap)	
Digital I/O	ISO IN (x1), ISO OUT (x2), TTL IN (x1), TTL IN OUT (2, selectable)		TTL IN (x3), TTL OUT (x3)	
General				
Lens Mount	C mount			
Flange Back	17.526 mm			
Power Requirements	DC +12 V (10.5 V to 15.0 V), PoCL (10 V to 13.0 V)			
Power Consumption	5.0 W max. (DC +12V)**3		2.7 W max. (DC +12V)	
Operating Temperature	-5°C to +45°C (23°F to 113°F)			
Performance Guarantee Temperature	0°C to 40°C (32°F to 104°F)			
Storage Temperature	-30°C to +60°C (-22°F to +140°F)			
Operating Humidity	20% to 80% (no condensation)			
Storage Humidity	20% to 95% (no condensation)			
Vibration Resistance	10 G (20 Hz to 200 Hz 20 minutes for each direction -x, y, z)			
Shock Resistance	70 G			
Dimensions (W x H x D)	44 x 44 x 30 mm (excluding protrusions) 13/4 x 13/4 x 13/16 inches (excluding protrusion)		29 x 29 x 30 mm (excluding protrusions) 13/16 x 13/16 x 13/16 inches (excluding protrusion)	
Mass	Approx. 96 g (Approx. 3.4 oz)		Approx. 53 g (Approx. 1.9 oz)	
MTBF	70,523 hours (Approx. 8.1 years)		81,562 hours (Approx. 9.3 years)	
Regulations	UL60950-1, FCC Class A, CSA C22.2-No. 60950-1, IC Class A Digital Device, CE : EN61326 (Class A), AS EMC : EN61326-1, VCCI Class A, KCC			
Supplied Accessories	Lens mount cap (1), Operating instructions (1)			

*1 The frame rate does not change. *2 A feature valid when the wide dynamic range feature is ON.

*3 When supplying power (PoCL) with 1 camera cable, wide dynamic range, frame accumulation, and area exposure features are not available for use.

Distributed by

©2017 Sony Imaging Products & Solutions Inc. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. "SONY" is a registered trademark of Sony Corporation. Pregius and Exmor R are trademark of Sony Corporation. All other trademarks are the property of their respective owners. Please visit Sony's professional website or contact your Sony representative for specific models available in your region.
PHC_03/10/2017

SONY